

General Description

The Digital Blocks DB-RTP-UDP-IP-AV IP Core is a RTP/UDP/IP Protocol Hardware Stack with MAC Layer Pre- & Post-Processors and an ARP Packet Processor targeting low latency, full off-load from a processor, of Audio/Video Packet Processing. The DB-RTP-UDP-IP-AV is a Verilog SoC IP Core targeting Xilinx/Altera/Lattice FPGAs and ASIC/ASSP devices.

Figure 1 depicts the RTP/UDP/IP Protocol Hardware Stack SoC IP Core embedded within an FPGA/ASSP/ASIC device, connected on one side to a 10/100 MbE or 1/10/40 Gigabit Ethernet MAC, and on the other side to the user application, such as H.264/H.265 CODECs.




Figure 1: DB-RTP-UDP-IP-AV – RTP/UDP/IP Hardware Stack for Audio/Video Applications

Features

- 10/100 MbE as well as 10/40 Gb wire-line performance with ultra-low latency of Audio/Video encapsulated within an IP/UDP/RTP packet
- Address Resolution Protocol (ARP) Packet Processor (client/server) with 4-16 entry ARP cache
- Internet Protocol (IP) Packet Processor:
 - IPv4 and IPv6 (optional) & ICMP (Internet Control Message Protocol) Protocol
 - IP header checksum generator (transmitter) & check (receiver), user-selectable Maximum Transmission Unit (MTU), Unicast, Broadcast & Multicast Packet support
 - Compliance with IETF IPv4/IPv6 RFCs
- User Datagram Protocol (UDP) Packet Processor:
 - Support for up to 256 UDP Ports
 - UDP header checksum generator (transmitter) & check (receiver)
 - Compliance with IETF UDP RFCs
- Real Time Transport Protocol (RTP) Packet Processor
 - Encapsulates (transmitter) /Decapsulates (receiver) H.264/NAL streams to RTP packets
 - Compliance with IETF RTP RFCs
- High Speed Data Interface to user Host Application:
 - 10 GbE: 64-bit @ 156.25 MHz AXI4-Stream or Avalon-ST
 - 40 GbE: 128-bit @ 312.50 MHz AXI4-Stream or Avalon-ST
- Host set-up & control via Control & Status Registers and Interrupt Controller
 - 32-bit @ user clock rate AXI4-Lite or Avalon-MM
 - Optional hardwired setup
- Pipeline, High Clock Rate, Low Latency architecture & design
- Fully-synchronous, synthesizable RTL Verilog SoC IP core

Customer Evaluation

Digital Blocks offers a variety of methods for prospective customers to evaluate the RTP/UDP/IP Protocol Hardware Stack SoC IP Core. Please contact Digital Blocks for additional information.

Deliverables

The DB-RTP-UDP-IP-AV IP Core is available in synthesizable RTL Verilog or a technology-specific netlist for FPGAs, along with Synopsys Design Constraints, a simulation test bench with expected results, datasheet, and user manual.

Ordering Information

Please contact Digital Blocks for additional technical, pricing, evaluation, and support information.

Digital Blocks, Inc.
PO Box 192
587 Rock Rd
Glen Rock, NJ 07452 USA
Phone: +1-201-251-1281
eFax: +1-702-552-1905
info@digitalblocks.com

Copyright © Digital Blocks, Inc. 2012-2014, ALL RIGHTS RESERVED

###

Digital Blocks is a registered trademark of Digital Blocks, Inc.
All other trademarks are the property of their respective owners